

한양디지텍 WIFI 공유기 HYC-G800C



- 무선모드 802.11 b/g/n 지원
- 5 개의 이더넷 포트 (10/100 Base-T): 1 WAN & 4 LAN
- Wire speed 의 NAT 보장
- QoS 및 멀티캐스트 기능

주요기능 :

- ✓ 2T2R 802.11 b/g/n 모드 와이파이 AP
- ✓ Wire speed NAT with 5 Fast Ethernet ports :
1 WAN port & 4 PC/LAN ports
- ✓ 802.1q VLAN and Multicast(IGMP),
- ✓ DHCP 클라이언트 / 서버
- ✓ QoS (Rate Limiting, Classification, Marking, Scheduling)
- ✓ 시큐리티, 슈퍼 DMZ 기능
- ✓ 손쉬운 컨피그레이션 / 프로비저닝 / 펌웨어 업그레이드
- ✓ IEEE802.1x, WEB Authentication, WPS, 4SSIDs, WMM
- ✓ SNMPv2, Telnet, Embedded Web

스펙

Physical Index		Wireless	IEEE 802.11 b/g/n Coverage: Indoor 20M, Outdoor 50M IEEE 802.1x Authentication WPS 4 SSIDs 802.11e(WMM) Radius Interworking	
CPU	400 MHz high performance CPU			
Flash	8 MBytes Flash			
SDRAM	32 MBytes SDRAM			
Ethernet Interfaces	5 RJ-45 (Ethernet 10/100 Base-T) : 1 WAN and 4 PC/LAN ports			
Dimensions	(L) 180 x (W) 110 x (H) 35 mm			
Weight	450g (without package)			
Frequency	2.4~2.4835GHz			
Antenna	2T2R Input impedance 50 ohm , Gain 5dBi	QoS	Classification: physical port, 802.1p/Q SRC/DST IP address & port ,TOS/DSCP TCP/UDP support Rate Limit Marking Scheduling: SPQ + WRR	
Functional Specification			Security	Broadcast storm control Abnormal traffic control Ddos attack Port monitoring MAC filter, packet filter Firewall Untrust mode
Network	Ethernet : Auto-negotiation 1K MAC support 802.1q Vlan IGMP: snooping , join/leave, suppression Fast leave, IGMP proxy DHCP client/server NAT/Bridge Wire-speed NAT performance Port Forwarding , DMZ DDNS MAC Clone Bi-directional 500 session support	Management	Firmware Upgradable Web Management Interface IVR-driven Management Interface Local and Remote Syslog(RFC3164) Auto Provisioning SNTP Time Synchronization Multi User Level SNMP v2, Telnet, Embedded web	
		Electrical Specification		
		Power unit AC Power	DC 5V/2A AC/DC Adapter AC Input: 100~240V, 50~60Hz	

한양디지텍(주) IP 통신사업부
경기도 화성시 반월동 103번지
전화 :070-4012-0017
팩스 :031-695-5090
E-mail : 장준상 차장 jsjang@hanyangdgt.com